


Cable fittings and accessories

Metal fitting with shield termination TOP-T-S-EMV



Properties

- Cable fitting with hexagon base
- Strain relief
- Gasket
- O-Ring and EMC compliant shield termination
- Simple installation - the shield braiding with plastic insert is pressed against fitting base

Technical data

Protection class IP 68 to 5 bar

Design

- Material Brass nickel-plated
- Sealing ring (DR) Neoprene
- O-Ring (OR) Perbunan®

Part-No.	Type	G	Clamping range D mm	SW = across flats mm	L 1 mm	D mm	weight approx. kg/100 piece	VE piece
TOP-T-S-EMV metric								
600170	TOP-T-S-EMV M 12 × 1.5	M 12	3.0 – 6.5	14	5.0	5.2	1.21	100
600171	TOP-T-S-EMV M 16 × 1.5	M 16	5.5 – 10.0	17	5.5	8.2	1.67	100
600172	TOP-T-S-EMV M 20 × 1.5	M 20	8.0 – 13.0	22	6.0	11.5	2.88	50
600173	TOP-T-S-EMV M 25 × 1.5	M 25	11.0 – 18.0	30	7.0	15.2	6.03	25
600174	TOP-T-S-EMV M 32 × 1.5	M 32	15.0 – 21.0	34	8.0	18.0	7.86	25
600175	TOP-T-S-EMV M 40 × 1.5	M 40	19.0 – 27.0	44	8.0	23.0	17.57	10
600176	TOP-T-S-EMV M 50 × 1.5	M 50	26.0 – 35.0	55	9.0	31.0	28.82	5
600177	TOP-T-S-EMV M 63 × 1.5	M 63	39.0 – 48.0	66	10.0	31.0	35.88	5
TOP-T-S-EMV PG								
600520	TOP-T-S-EMV PG 7	PG 7	3.0 – 6.5	14	5.0	5.0	1.20	100
600521	TOP-T-S-EMV PG 9	PG 9	5.5 – 10.0	17	6.0	7.5	1.70	100
600522	TOP-T-S-EMV PG 11	PG 11	5.5 – 10.0	20	6.0	9.5	3.37	50
600523	TOP-T-S-EMV PG 13.5	PG 13,5	8.0 – 13.0	22	6.5	11.5	3.52	50
600524	TOP-T-S-EMV PG 16	PG 16	8.0 – 14.0	24	6.5	12.0	3.64	50
600525	TOP-T-S-EMV PG 21	PG 21	11.0 – 18.0	30	7.0	17.5	7.10	25
600526	TOP-T-S-EMV PG 29	PG 29	19.0 – 27.0	40	8.0	25.0	12.20	25
600527	TOP-T-S-EMV PG 36	PG 36	24.0 – 32.0	50	9.0	31.5	15.10	10
600528	TOP-T-S-EMV PG 42	PG 42	30.0 – 38.0	57	10.0	37.5	21.10	5
600529	TOP-T-S-EMV PG 48	PG 48	34.0 – 44.0	64	10.0	43.5	30.00	5