



















Pegasus

Emergency push buttons

EN418

	DESCRIPTION	COLOUR	REF. NO.	WEIGHT g	MIN. PACK QTY.	DIMENSIONS
	Mushroom operator Ø 30 twist to release		PPFN1R3N	42	10	
	Mushroom operator with vision Ø 30 twist to release		PPFN1R3S	44	10	
	Mushroom operator Ø 40 twist to release		PPFN1R4N	44	10	
	Mushroom operator with vision Ø 40 twist to release		PPFN1R4S	46	10	
	Mushroom operator Ø 60 twist to release		PPFN1R6N	50	10	
	Mushroom operator with vision Ø 60 twist to release		PPFN1R6S	52	10	









Pegasus

Emergency push buttons

EN418



TECHNO-CONTROL EQUIPMENT

	DESCRIPTION	COLOUR	REF. NO.	WEIGHT g	MIN. PACK QTY.	DIMENSIONS
	Mushroom operator ø 40 with key release	■	PPFN1C4N	76	10	
	Mushroom operator ø 40 push-pull	■	PPFN1P4N	44	10	
	Mushroom operator ø 40 push-pull with vision	■	PPFN1P4S	46	10	
	Mushroom operator ø 40 push-pull with colour cap	■	PPFN1P4C	45	10	
	Mushroom operator ø 40 push-pull with lens cap	■	PPFL1P4N	45	10	


TECHNICAL NOTES

All operators comply with the relevant European standard

EN418 Machine safety
Emergency stop operators, functional characteristics – Design guidelines

IEC/EN60947-5-1

Comply with the standard
IEC/EN60204-1: Machine safety –
Machine electrical circuits –
General guidelines

- The push buttons are designed with a load charge mechanism to ensure a reliable operation and stoppage, or blockage, in the activated position. The combination with positive switching NC  contacts and the presence of the "status" indicator on some models, guarantee a high degree of reliability and effectiveness.