

Limit Switches

Pre-wired FCT series

IP67 □ thermoplastic type



TECHNO-CONTROL EQUIPMENT

Cable: PVC UL
5x0.75 mm²
2 m length
Outlet : horizontal .L.
vertical .V.



.01.



.02.



.03.



.04.

TYPE OF OPERATOR	STEEL END PLUNGER	ROLLER PLUNGER	90° ROLLER PLUNGER	14 Ø POM ROLLER LEVER
X11 1NC-1NO 	FCT2L01X11 FCT2V01X11 	FCT2L02X11 FCT2V02X11 	FCT2L03X11 FCT2V03X11 	FCT2L04X11 FCT2V04X11
WEIGHT gr. – MIN. PACK QTY.	75 gr. 1 pcs.	78 gr. 1 pcs.	80 gr. 1 pcs.	80 gr. 1 pcs.
DIMENSIONS				

Cable: PVC UL
5x0.75 mm²
2 m length
Outlet : horizontal .L.
vertical .V.



.06.



.07.



.08.

TYPE OF OPERATOR	STEEL END PLUNGER WITH THREADED FLANGE	ROLLER PLUNGER WITH THREADED FLANGE	90° ROLLER PLUNGER WITH THREADED FLANGE	CHARACTERISTICS
X11 1NC-1NO 	FCT2L06X11 FCT2V06X11 	FCT2L07X11 FCT2V07X11 	FCT2L08X11 FCT2V08X11 	IEC/EN60947-5-1 Rated insulation voltage Ui/500V Rated thermal current Ith 10A Rated operating current Ie: AC15 Ue V 120 250 400 Ie A 6 4 3 DC13 Ue V 24 125 250 Ie A 2,5 0,55 0,27 UL508 General use Designation A300-G300 Operating temperature -25 +70 °C Self extinguishing body VO
WEIGHT gr. – MIN. PACK QTY.	75 gr. 1 pcs.	78 gr. 1 pcs.	80 gr. 1 pcs.	
DIMENSIONS				