


# Function module · Varioprint Mounting Module

Mounting module with soldering terminals for free component fitting of assembly parts  
 AC/DC 250 V, 4A  
 Screw-/spring terminal




Description	Part-No.					Type	PU
<b>Screw terminal</b>							
Number of solder lugs	6	12	18	24	30	MPE-3-0620	5
						MPE-6-0626	5
						MPE-9-0828	2
						MPE-12-0663	5
						MPE-15-0664	5
<b>Technical data</b>							
	<b>6</b>	<b>12</b>	<b>18</b>	<b>24</b>	<b>30</b>		
Function type	Subplate						
Pin spacing	4.5 mm			5 mm			
Nominal voltage	AC/DC 250 V						
Rated current	4 A						
Rated insulation voltage (EN 40178)	300 V						
Pollution degree	2						
Overvoltage category	I						
<b>General</b>							
Housing material	PPE						
Protection class	IP 00						
Field installation	rail TS 35 (EN 50022)						
Operation temperature range	-25 °C – 70 °C						
Storage temperature range	-40 °C – 80 °C						
Dimensions (w × h × d)	17.5 × 78.0 × 4	35.0 × 78.0 × 4	45.0 × 78.0 × 4	65.0 × 78.0 × 4	80.0 × 78.0 × 4		
	5.0 mm	5.0 mm	5.0 mm	5.0 mm	5.0 mm		
Weight (kg/piece)	0.028	0.048	0.068	0.095	0.125		
Approvals	-						
Termination	Screw terminal: 0.08–2.5 mm <sup>2</sup>						

## Dimensions



## PIN assignment

710620, 710626, 710828



710663, 710664

