

Cable fittings and accessories

LÜTZE CABLEFIX® X Cable Entry System for cables



Technical data

Protection class	IP65
Temperature range	-40 °C ... +80 °C
Burning behavior according to	UL 94 HB
Oil resistant according to	UL/NEMA Typ 13

Application

- Feed-through system for unassembled cables

Properties

- Simple and quick to install: cables are inserted by pushing the end through the seal from the front. Snap-in design for enclosures with a 1.5 mm wall thickness. Provides up to 80 % time savings compared to using individual cable glands.
- Integrated seal protects up to UL Type 4X, 12, 13 and IP65
- Compact design with improved cable density: up to 50% space savings compared to individual cable glands
- Wide clamping ranges allow for use with cables with various outer diameters
- Entry points are sealed by default, eliminating the need for blanking plugs.
- Cable entry points open without any tools when inserting the cable from the front.
- Acc. to UL 50E and 508A

Construction

- Material: PA 6 glass fiber reinforced
- Color: black

Part-No.	Type	Number of cables × cable diameter	Dimensions (w × h × d) mm	Cut-out (B×H)	Approvals	PU piece
LÜTZE CABLEFIX® X Snap-In						
606561	S* CABLEFIX X 12 Snap-In	12 × 5 – 13 mm	148.0 × 60.0 × 13.5	112 × 36 mm	UL Type 4X (∅ 5 – 13 mm) UL Type 12/13 (∅ 4 – 13 mm) UL CCN NITW2 NITW8	1
606562	S* CABLEFIX X 23 Snap-In	23 × 4 – 8.5 mm	148.0 × 60.0 × 13.5	112 × 36 mm	UL Type 12 UL Type 13 UL CCN NITW2 NITW8	1