

# Cable fittings and accessories

## Plastic fittings TOP-T-P, metric version



### Properties


- – metric –
- Cable fitting with hexagon base
- Strain relief and seal

### Technical data

Protection class IP 68 to 5 bar

### Design

- Material Polyamide PA 6.6-V-2
- Colour grey RAL 7001  
black RAL 9005
- Gasket Neoprene



Part-No.	Type	G	Approvals	Clamping range D mm	SW mm	L 1 mm	weight approx. kg/100 piece	PU piece
<b>TOP-T-P metric grey RAL 7001</b>								
600790	TOP-T-P M 12x1,5	M 12x1.5	UR	2.0 – 6.5 mm	15	8.0	0.32	100
600680	TOP-T-P M 16x1,5	M 16x1.5	UR	4.0 – 10.0 mm	20	8.0	0.57	100
600681	TOP-T-P M 20x1,5	M 20x1.5	UL	6.0 – 12.0 mm	24	9.0	0.96	100
600682	TOP-T-P M 25x1,5	M 25x1.5	UL	9.0 – 16.0 mm	28	11.0	1.55	50
600683	TOP-T-P M 32x1,5	M 32x1.5	UL	11.0 – 21.0 mm	36	11.0	2.65	25
600791	TOP-T-P M 40x1,5	M 40x1.5	UL	16.0 – 28.0 mm	46	11.0	4.34	10
600792	TOP-T-P M 50x1,5	M 50x1.5	UR	27.0 – 35.0 mm	55	13.0	6.80	5
600684	TOP-T-P M 63x1,5	M 63x1.5		32.0 – 42.0 mm	68	14.0	9.60	5
<b>TOP-T-P metric black RAL 9005</b>								
600840	TOP-T-P M 12x1,5	M 12x1.5	UR	2.0 – 6.5 mm	15	8.0	0.32	100
600841	TOP-T-P M 16x1,5	M 16x1.5	UR	4.0 – 10.0 mm	20	8.0	0.57	100
600842	TOP-T-P M 20x1,5	M 20x1.5	UL	6.0 – 12.0 mm	24	9.0	0.96	100
600843	TOP-T-P M 25x1,5	M 25x1.5	UL	9.0 – 16.0 mm	28	11.0	1.55	50
600844	TOP-T-P M 32x1,5	M 32x1.5	UL	10.0 – 21.0 mm	36	11.0	2.65	25
600845	TOP-T-P M 40x1,5	M 40x1.5	UL	16.0 – 28.0 mm	46	11.0	4.40	10
600846	TOP-T-P M 50x1,5	M 50x1.5	UL	21.0 – 34.5 mm	53	13.0	7.37	5
600847	TOP-T-P M 63x1,5	M 63x1.5		30.0 – 44.5 mm	65	14.0	10.26	5

# Cable fittings and accessories

## Plastic fittings TOP-T-P, PG version



### Properties


- – PG –
- Cable fitting with hexagon base
- Strain relief and seal

### Technical data

Protection class IP 68 to 5 bar

### Design


- Material polyamide PA 6.6-V-2
- Colour Grey RAL 7001 and Black RAL 9005
- Gasket Neoprene



Part-No.	Type	G	Approvals	Clamping range D mm	SW mm	L 1 mm	weight approx. kg/100 piece	PU piece
<b>TOP-T-P PG grey RAL 7001</b>								
600660	TOP-T-P PG 7	PG 7		3.0 – 6.5 mm	15	8.0	0.33	100
600661	TOP-T-P PG 9	PG 9		4.0 – 8.0 mm	19	8.0	0.52	100
600662	TOP-T-P PG 11	PG 11	UR	5.0 – 10.0 mm	22	8.0	0.87	100
600663	TOP-T-P PG 13,5	PG 13,5	UL	6.0 – 12.0 mm	24	9.0	0.96	100
600664	TOP-T-P PG 16	PG 16	UL	10.0 – 14.0 mm	27	10.0	1.37	50
600665	TOP-T-P PG 21	PG 21	UL	13.0 – 18.0 mm	33	11.0	2.04	50
600666	TOP-T-P PG 29	PG 29	UL	18.0 – 25.0 mm	42	11.0	3.88	25
600667	TOP-T-P PG 36	PG 36	UL	22.0 – 34.0 mm	53	13.0	6.90	10
600668	TOP-T-P PG 42	PG 42	UL	30.0 – 38.0 mm	60	13.0	8.80	5
600669	TOP-T-P PG 48	PG 48	UL	34.0 – 44.0 mm	65	14.0	9.79	5
<b>TOP-T-P PG black RAL 7005</b>								
600860	TOP-T-P PG 7	PG 7		3.0 – 6.5 mm	15	8.0	0.33	100
600861	TOP-T-P PG 9	PG 9		4.0 – 8.0 mm	19	8.0	0.52	50
600862	TOP-T-P PG 11	PG 11	UR	5.0 – 10.0 mm	22	8.0	0.87	100
600863	TOP-T-P PG 13,5	PG 13,5	UL	6.0 – 12.0 mm	24	9.0	0.96	50
600864	TOP-T-P PG 16	PG 16	UL	10.0 – 14.0 mm	27	10.0	1.37	50
600865	TOP-T-P PG 21	PG 21	UL	13.0 – 18.0 mm	33	11.0	2.04	50
600866	TOP-T-P PG 29	PG 29	UL	18.0 – 25.0 mm	42	11.0	3.98	25
600867	TOP-T-P PG 36	PG 36	UL	22.0 – 34.0 mm	53	13.0	6.90	10
600868	TOP-T-P PG 42	PG 42	UL	30.0 – 38.0 mm	60	13.0	8.80	5
600869	TOP-T-P PG 48	PG 48	UL	34.0 – 44.0 mm	65	14.0	9.79	5

# Cable fittings and accessories

## Plastic fitting TOP-TR-P



### Properties

- Cable fitting with hexagon base
- Strain relief and gasket
- Reduced sealing insert
- Reduced clamping range

### Technical data

Protection class IP 68 to 5 bar  
 Approvals on request

### Design

- Material Polyamide PA 6-V-2
- Colour grey RAL 7001  
other colours upon request
- Gasket NBR

Part-No.	Type	G	Approvals	Clamping range D mm	SW mm	L 1 mm	weight approx. kg/100 piece	PU piece
<b>TOP-TR-P metric</b>								
600690	TOP-TR-P M 16x1,5	M 16x1.5	on request	2.0 – 7.0 mm	20	8.0	0.62	100
600691	TOP-TR-P M 20x1,5	M 20x1.5	on request	4.0 – 10.0 mm	24	8.0	1.34	100
600692	TOP-TR-P M 25x1,5	M 25x1.5	on request	5.0 – 14.0 mm	29	8.0	1.63	50
600693	TOP-TR-P M 32x1,5	M 32x1.5	on request	8.0 – 18.0 mm	36	10.0	2.72	25
600794	TOP-TR-P M 12x1,5	M 12x1.5	on request	2.0 – 5.0 mm	15	8.0	0.33	100

# Cable fittings and accessories

## Plastic accessories locknut GK, metric version




### Properties

- – metric –
- Counter nut, hexagonal, with metric thread according to DIN 46320

### Design

- Material Polyamide 6 GF 30
- Colour grey RAL 7001  
black RAL 9005  
other colour upon request



Part-No.	Type	G	SW mm	S mm	weight approx. kg/100 piece	PU piece
<b>GK metric grey RAL 7001</b>						
600398	GK M 12x1,5	M 12x1.5	17	5.0	0.10	100
600391	GK M 16x1,5	M 16x1.5	22	5.0	0.16	100
600392	GK M 20x1,5	M 20x1.5	26	6.0	0.23	100
600393	GK M 25x1,5	M 25x1.5	32	6.0	0.28	100
600394	GK M 32x1,5	M 32x1.5	41	7.0	0.41	100
600395	GK M 40x1,5	M 40x1.5	50	7.0	0.67	50
600396	GK M 50x1,5	M 50x1.5	60	8.0	1.14	50
600698	GK M 63x1,5	M 63x1.5	75	8.0	1.95	50
<b>GK metric black RAL 9005</b>						
600850	GK M 12x1,5	M 12x1.5	17	5.0	0.10	100
600851	GK M 16x1,5	M 16x1.5	22	5.0	0.14	100
600852	GK M 20x1,5	M 20x1.5	26	6.0	0.22	100
600853	GK M 25x1,5	M 25x1.5	32	6.0	0.26	100
600854	GK M 32x1,5	M 32x1.5	41	7.0	0.38	100
600855	GK M 40x1,5	M 40x1.5	50	7.0	0.63	50
600856	GK M 50x1,5	M 50x1.5	60	8.0	1.14	50
600857	GK M 63x1,5	M 63x1.5	75	8.0	1.78	50

# Cable fittings and accessories

## Plastic accessory locknut GK, PG version




### Properties

- – PG –
- Counter nut, hexagonal, with armour threads according to DIN 46320.

### Design

- Material Polyamide 6 GF 30
- Colour grey RAL 7001  
black RAL 9005  
other colors available on request



Part-No.	Type	G	SW mm	S mm	weight approx. kg/100 piece	PU piece
<b>GK PG grey RAL 7001</b>						
600430	GK PG 7	PG 7	19	5.0	0.13	100
600431	GK PG 9	PG 9	22	5.0	0.14	100
600432	GK PG 11	PG 11	24	5.0	0.15	100
600433	GK PG 13,5	PG 13.5	27	6.0	0.24	100
600434	GK PG 16	PG 16	30	6.0	0.31	100
600435	GK PG 21	PG 21	36	7.0	0.45	100
600436	GK PG 29	PG 29	46	7.5	0.68	50
600437	GK PG 36	PG 36	60	8.0	1.47	50
600438	GK PG 42	PG 42	65	8.0	1.53	50
600439	GK PG 48	PG 48	70	8.0	1.71	50
<b>GK PG black RAL 9005</b>						
600830	GK SW PG 7	PG 7	19	5.0	0.13	100
600831	GK SW PG 9	PG 9	22	5.0	0.14	100
600832	GK SW PG 11	PG 11	24	5.0	0.15	100
600833	GK SW PG 13,5	PG 13.5	27	6.0	0.24	100
600834	GK SW PG 16	PG 16	30	6.0	0.31	100
600835	GK SW PG 21	PG 21	36	7.0	0.45	100
600836	GK SW PG 29	PG 29	46	7.5	0.68	100
600837	GK SW PG 36	PG 36	60	8.0	1.47	50
600838	GK SW PG 42	PG 42	65	8.0	1.53	50
600839	GK SW PG 48	PG 48	70	8.0	1.71	50