

Cable fittings and accessories

Plastic and metal accessories multiple sealing insert MFDE



Application

- For retroactive installation in our cable fittings Type Top T in plastic and brass, if necessary these are to be drilled yourself depending on needs
- PG 11 suitable for M 16
PG 13.5 suitable for M 20
PG 16 suitable for M 25
PG 21 suitable for M 32

Properties

- Multiple sealing insert for two or more cables in a fitting


Design

- Material TPE

Part-No.	Type	Outer-Ø mm	Number of cables x Ø mm	weight approx. kg/100 piece	PU piece
MFDE PG					
600626	MFDE PG 9	10.0	2 x 3.0	0.57	100
600627	MFDE PG 9	10.0	4 x 3.0	0.46	100
600541	MFDE PG 9	10.0	0 x 0.0	0.70	100
600628	MFDE PG 11	13.0	2 x 4.0	1.00	100
600629	MFDE PG 11	13.0	2 x 4.5	0.80	100
600635	MFDE PG 11	13.0	3 x 4.0	0.10	100
600636	MFDE PG 11	13.0	3 x 5.0	0.70	100
600542	MFDE PG 11	13.0	0 x 0.0	0.11	100
600638	MFDE PG 13.5	15.0	2 x 4.5	1.32	100
600639	MFDE PG 13.5	15.0	2 x 5.0	1.20	100
600640	MFDE PG 13.5	15.0	2 x 6.0	1.20	100
600637	MFDE PG 13.5	15.0	3 x 4.0	1.40	100
600630	MFDE PG 13.5	15.0	3 x 5.0	1.20	100
600543	MFDE PG 13.5	15.0	0 x 0.0	1.60	100
600641	MFDE PG 16	17.0	2 x 4.0	2.00	100
600644	MFDE PG 16	17.0	2 x 6.0	1.78	100
600631	MFDE PG 16	17.0	3 x 4.0	1.92	100
600643	MFDE PG 16	17.0	3 x 5.0	1.60	100
600646	MFDE PG 16	17.0	4 x 6.0	1.20	100
600633	MFDE PG 16	17.0	5 x 4.0	1.62	100
600544	MFDE PG 16	17.0	0 x 0.0	2.30	100
600645	MFDE PG 16	17.0	3 x 6.0	1.00	100
600647	MFDE PG 16	17.0	3 x 6.5	1.20	100
600642	MFDE PG 16	17.0	4 x 4.0	1.73	100
600632	MFDE PG 16	17.0	4 x 5.0	1.20	100
600648	MFDE PG 21	22.0	2 x 7.0	3.60	100
600651	MFDE PG 21	22.0	2 x 8.0	3.20	100
600653	MFDE PG 21	22.0	2 x 9.0	3.20	100
600649	MFDE PG 21	22.0	3 x 7.0	3.00	100
600652	MFDE PG 21	22.0	3 x 8.0	2.65	100
600634	MFDE PG 21	22.0	4 x 7.0	2.60	100
600545	MFDE PG 21	22.0	0 x 0.0	5.60	100
600656	MFDE PG 29	29.5	5 x 8.5	6.00	100
600654	MFDE PG 29	29.5	6 x 5.0	7.70	100
600655	MFDE PG 29	29.5	8 x 5.0	7.40	100
600546	MFDE PG 29	29.5	0 x 0.0	9.80	100

Cable fittings and accessories

Plastic and metal accessory sealing insert ASI DE



Application

- For retroactive installation of our cable fittings
- **Cable dimensions:** 4.0 mm x 10.0 mm +/- 0.2 mm
- **Suitable for installation with the following types:**
 - TOP TP PG 13.5
 - TOP TP M 20
 - TOP T PG 13.5
 - TOP T M 20

Properties

- Seal insert for ASI bus cables

Design

- Material TPE

Part-No.	Type	Outer-Ø mm	weight approx. kg/100 piece	PU piece
ASI DE				
600120	ASI DE PG 13.5	14.8	0.15	1